



FLECK® 5000SXT HIGH PERFORMANCE CONTROL VALVE

PROGRAMMING EASE WITH OPTIONS FOR FILTER AND SOFTENER APPLICATIONS



FEATURES/BENEFITS

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Continuous service flow rate of 21 GPM with a backwash of 17 GPM

Backwash capability accommodates softener tanks up to 16" and filter up to 16" in diameter

Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment system

Super capacitor for keeping time of day during power outage

Time-tested, hydraulically-balanced piston for service and regeneration

Soft water refill for a cleaner brine tank

Diagnostics for historical valve performance

Programming stored in memory and will not be lost due to power outages

OPTIONS

Filter or softener control valves

Downflow co-current or upflow counter-current regeneration

Brine cam auxiliary switch

Plumbing connections in 3/4" to 1-1/4" NPT, BSP, and sweat

Fiber-reinforced polymer or stainless steel bypass valve

SXT- Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.



TESTED and CERTIFIED by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.



UL recognized to 979



Restriction of Hazardous Substance Compliant

VALVE SPECIFICATIONS

Valve Material	Fiber-reinforced polymer
Inlet/Outlet	3/4", 1", or 1-1/4" NPT/ BSP/Sweat
Cycles	5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi drop	21 GPM (4.8 m ³ /h)
Peak 25 psi drop	27 GPM (6.1 m ³ /h)
Cv flow at 1 psi drop	5.4
Max. Backwash 25 psi drop	17 GPM (3.9 m ³ /h)

REGENERATION

Downflow/Upflow	Both
Adjustable Cycles	Yes
Time Available SXT:	0 - 199 min/cycle

METER INFORMATION

Meter Accuracy 3/4" Paddle/Turbine:	0.25 - 15 GPM ± 5% (0.06 - 3 m ³ /h)
Meter Capacity Range SXT:	1 - 999,900 gal (0 - 3,785 m ³)

DIMENSIONS

Distributor Pilot	1.05" O.D. (26.7 mm)
Drain Line	1/2" NPTF Quick-Connect
Brine Valve 1600:	3/8"
Injector System	1610
Mounting Base	2.5" – 8 NPSM
Height from Top of Tank	8" (203 mm)
Riser Tube Diameter	3/4" (19 mm)
Riser Height	Flush with top of tank

TYPICAL APPLICATIONS

Water Softener	6 - 16" diameter
Filters	6 - 16" diameter based on 10 GPM/ft ²

ADDITIONAL INFORMATION

Electrical Rating	110/220V 50/60 Hz
Max. VA	8.4
Estimated Shipping Weight	
Time Clock:	8 lbs
Metered Valve:	9 lbs
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | WWW.PENTAIRAQUA.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

42960 REV C JL14 © 2013 Pentair Residential Filtration, LLC. All Rights Reserved.